



| Model Ref. | Power (tcW) | Lumens (P/W) | Luminaire Output (lm) | Colour | Dimension | IP Rating | Up / Down Light |
|------------|-------------|--------------|-----------------------|--------|------------------------|-----------|-----------------|
| SLA/9W/3K | 9 | 88 | 800 | 3000K | ∅ 400mm x 110mm x 81mm | IP20 | Yes |
| SLA/9W/4K | 9 | 91 | 825 | 4000K | ∅ 400mm x 110mm x 81mm | IP20 | Yes |
| SLA/16W/3K | 16 | 93 | 1500 | 3000K | ∅ 400mm x 110mm x 81mm | IP20 | Yes |
| SLA/16W/4K | 16 | 97 | 1550 | 4000K | ∅ 400mm x 110mm x 81mm | IP20 | Yes |
| SLA/24W/3K | 24 | 90 | 2150 | 3000K | ∅ 400mm x 110mm x 81mm | IP20 | Yes |
| SLA/24W/4K | 24 | 94 | 2250 | 4000K | ∅ 400mm x 110mm x 81mm | IP20 | Yes |

Key Features

- Decorative LED wall light
- Bidirectional light output
- Opal acrylic diffusers for homogenous illumination
- Vertical or horizontal mounting
- Integral LED driver
- White (RAL9016) as standard, black (RAL9005) option available
- Short circuit, overload and temperature protection
- 5 year warranty

Please select from the options below

| | |
|----------------------|-----------|
| Dali | /DA |
| Switch Dim / Mains | /SD |
| DSI | /DSI |
| Emergency | /EM |
| Dali Emergency | /DA/EM |
| DALI Emergency Empro | /DA/EMPRO |
| Black Body | /BLK |

