

Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	IP Rating	Up / Down Light
SLA/9W/3K	9	88	800	830	∅ 400mm x 110mm x 81mm	IP65	Yes
SLA/9W/4K	9	91	825	840	∅ 400mm x 110mm x 81mm	IP65	Yes
SLA/16W/3K	16	93	1500	830	∅ 400mm x 110mm x 81mm	IP65	Yes
SLA/16W/4K	16	97	1550	840	∅ 400mm x 110mm x 81mm	IP65	Yes
SLA/24W/3K	24	90	2150	830	∅ 400mm x 110mm x 81mm	IP65	Yes
SLA/24W/4K	24	94	2250	840	∅ 400mm x 110mm x 81mm	IP65	Yes

Key Features

- Decorative LED wall light
- Bidirectional light output
- Opal acrylic diffusers for homogenous illumination
- Vertical or horizontal mounting
- Integral LED driver
- White (RAL9016) as standard, black (RAL9005) option available
- Short circuit, overload and temperature protection
- 5 year warranty

Please select from the options below

Dali	/DA
Switch Dim / Mains	/SD
DSI	/DSI
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Black Body	/BLK

