



Model Ref.	Total Power (tcW)	Lumens (P/W)	Total Luminaire Output (lm)	Colour	Dimension	Cut Out	IP Rating
CULL/6W/3K/SQ2	12	114	1368	3000K	∅ 185mm x 115mm x 80mm	90mm x 170mm	IP65
CULL/6W/4K/SQ2	12	115	1380	4000K	∅ 185mm x 115mm x 80mm	90mm x 170mm	IP65
CULL/9W/3K/SQ2	18	122	2196	3000K	∅ 185mm x 115mm x 105mm	90mm x 170mm	IP65
CULL/9W/4K/SQ2	18	124	2240	4000K	∅ 185mm x 115mm x 105mm	90mm x 170mm	IP65
CULL/13W/3K/SQ2	26	127	3302	3000K	∅ 185mm x 115mm x 115mm	90mm x 170mm	IP65
CULL/13W/4K/SQ2	26	128	3340	4000K	∅ 185mm x 115mm x 115mm	90mm x 170mm	IP65
CULL/18W/3K/SQ2	36	111	3996	3000K	∅ 185mm x 115mm x 135mm	90mm x 170mm	IP65
CULL/18W/4K/SQ2	36	113	4100	4000K	∅ 185mm x 115mm x 135mm	90mm x 170mm	IP65

### Key Features

- Professional downlight with a wide choice of options
- Single Colour Type
- Beam Spread 55 degree As Standard
- Power Factor 0.95
- 5 Year Warranty
- 50,000 Hours
- High Grade 6063 Aluminium Housing Material

### Please select from the options below

Dali	/DA
Switch Dim / Mains	/SD
DSI	/DSI
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Black Bezel	/BLK

