



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	Length
HIL/UD/600/3K	20	94	1850	3000K	∅ 72mm x 90mm	600mm
HIL/UD/600/4K	20	95	1900	4000K	∅ 72mm x 90mm	600mm
HIL/UD/1200/3K	40	94	3750	3000K	∅ 72mm x 90mm	1200mm
HIL/UD/1200/4K	40	95	3800	4000K	∅ 72mm x 90mm	1200mm
HIL/UD/1500/3K	50	94	4700	3000K	∅ 72mm x 90mm	1500mm
HIL/UD/1500/4K	50	95	4750	4000K	∅ 72mm x 90mm	1500mm
HIL/UD/1800/3K	60	94	5685	3000K	∅ 72mm x 90mm	1800mm
HIL/UD/1800/4K	60	95	5700	4000K	∅ 72mm x 90mm	1800mm
HIL/UD/2400/3K	80	94	7550	3000K	∅ 72mm x 90mm	2400mm
HIL/UD/2400/4K	80	95	7600	4000K	∅ 72mm x 90mm	2400mm

Key Features

- Extruded direct/indirect linear profile luminaire
- Typical percentage output ratio 75 : 25
- Comes complete with suspended mount fixings
- Finished in RAL 9006 grey as standard
- Available in 4 standard lengths
- Bespoke Lengths & Lumen outputs available on request
- Low glare prismatic lens available for office and LG7 compliance, please see Hilton 7575
- 2 m suspension kit

Please select from the options below

Dali	/DA
Switch Dim / Mains	/SD
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Suspended	/SUSP
Black Body	/BLK
White Body	/WHI

