



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	Cut Out	IP Rating
CULL/6W/3K/RF3	6	114	684	3000K	ø 78mm x 65mm	70mm	IP65
CULL/6W/4K/RF3	6	115	690	4000K	ø 78mm x 65mm	70mm	IP65
CULL/9W/3K/RF3	9	122	1098	3000K	ø 78mm x 90mm	70mm	IP65
CULL/9W/4K/RF3	9	124	1120	4000K	ø 78mm x 90mm	70mm	IP65
CULL/13W/3K/RF3	13	127	1651	3000K	ø 78mm x 97mm	70mm	IP65
CULL/13W/4K/RF3	13	128	1670	4000K	ø 78mm x 97mm	70mm	IP65
CULL/18W/3K/RF3	18	111	1998	3000K	ø 78mm x 115mm	70mm	IP65
CULL/18W/4K/RF3	18	113	2050	4000K	ø 78mm x 115mm	70mm	IP65

Key Features

- Professional downlight with a wide choice of options
- Single Colour Type
- Beam Spread 55 degree As Standard
- Power Factor 0.95
- 5 Year Warranty
- 50,000 Hours
- High Grade 6063 Aluminium Housing Material

Please select from the options below

- Dali /DA
- Switch Dim / Mains /SD
- DSI /DSI
- Emergency /EM
- Dali Emergency /DA/EM
- DALI Emergency Empro /DA/EMPRO
- Black Bezel /BLK

