



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	Beam Angle	IP Rating
GOUD/D/20W/3K	20	102	2050	3000K	∅ 100mm x 85mm	20-55	IP20
GOUD/D/20W/4K	20	105	2100	4000K	∅ 100mm x 85mm	20-55	IP20
GOUD/D/20W/3K/DALI	20	102	2050	3000K	∅ 100mm x 112mm	20-55	IP20
GOUD/D/20W/4K/DALI	20	105	2100	4000K	∅ 100mm x 112mm	20-55	IP20

Key Features

- Professional track downlight with a wide choice of options
- Single Colour Type
- Beam Spread 20-55 degree Adjustable
- Power Factor 0.95
- 5 Year Warranty
- 50,000 Hours
- High Grade 6063 Aluminium Housing Material

Please select from the options below

- Emergency **/EM**
- Dali Emergency **/DA/EM**
- Dali Emergency Empro **/DA/EMPRO**
- White **/WHI**
- Live End **/LE**
- End Cap **/EC**
- Straight Connector **/SC**
- 90 Degree Connector **/90**
- Flexible Connector **/FC**
- Tee Connector **/TEE**
- Suspension Kit **/SUSP**
- Honeycomb Baffle **/HB**



Narrow beam reflector



Wide beam reflector

