



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	IP Rating	UGR Rating
ROB/2/20W/3K	20	130	2600	3000K	∅ 595mm x 73mm	IP44	18.7
ROB/2/20W/4K	20	136	2725	4000K	∅ 595mm x 73mm	IP44	18.9
ROB/2/25W/3K	25	128	3200	3000K	∅ 595mm x 73mm	IP44	19.4
ROB/2/25W/4K	25	134	3350	4000K	∅ 595mm x 73mm	IP44	19.6
ROB/2/30W/3K	30	124	3725	3000K	∅ 595mm x 73mm	IP44	20
ROB/2/30W/4K	30	130	3900	4000K	∅ 595mm x 73mm	IP44	20.1
ROB/2/35W/3K	35	122	4300	3000K	∅ 595mm x 73mm	IP44	20.5
ROB/2/35W/4K	35	128	4500	4000K	∅ 595mm x 73mm	IP44	20.6
ROB/2/40W/3K	40	123	4925	3000K	∅ 595mm x 73mm	IP44	20.9
ROB/2/40W/4K	40	128	5150	4000K	∅ 595mm x 73mm	IP44	21.1

**Key Features**

- LED illuminated 600 x 600 Modular
- Twin IP44 linear LED windows
- Excellent uniform light distribution
- Low glare variants
- Excellent efficacy to aid Part L compliance
- High output variants
- Life greater than 60,000 hours
- Dimming and emergency options
- Short circuit, overload and temperature protection

**Please select from the options below**

Dali	/DA
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
DSI	/DSI
Switch Dim	/SD

