

Model Ref.	Power (tcW)	Luminaire Output (lm)	Colour	Dimension	Cut Out	IP Rating
PAR/SQ1/8W/27K	8	600	927	∅ 85mm x 85mm	∅ 81mm x 81mm	IP44
PAR/SQ1/6.5W/3K	6.5	675	830	∅ 85mm x 85mm	∅ 81mm x 81mm	IP44
PAR/SQ1/6.5W/4K	6.5	700	840	∅ 85mm x 85mm	∅ 81mm x 81mm	IP44
PAR/SQ1/10W/27K	10	850	927	∅ 85mm x 85mm	∅ 81mm x 81mm	IP44
PAR/SQ1/8W/3K	8	850	830	∅ 85mm x 85mm	∅ 81mm x 81mm	IP44
PAR/SQ1/8W/4K	8	900	840	∅ 85mm x 85mm	∅ 81mm x 81mm	IP44
PAR/SQ2/16W/27K	16	1200	927	∅ 154mm x 85mm	∅ 145mm x 81mm	IP44
PAR/SQ2/13W/3K	13	1350	830	∅ 154mm x 85mm	∅ 145mm x 81mm	IP44
PAR/SQ2/13W/4K	13	1400	840	∅ 154mm x 85mm	∅ 145mm x 81mm	IP44
PAR/SQ2/20W/27K	20	1700	927	∅ 154mm x 85mm	∅ 145mm x 81mm	IP44
PAR/SQ2/16W/3K	16	1700	830	∅ 154mm x 85mm	∅ 145mm x 81mm	IP44
PAR/SQ2/16W/4K	16	1800	840	∅ 154mm x 85mm	∅ 145mm x 81mm	IP44
PAR/SQ3/24W/27K	24	1800	927	∅ 222mm x 85mm	∅ 213mm x 81mm	IP44
PAR/SQ3/19.5W/3K	19.5	2025	830	∅ 222mm x 85mm	∅ 213mm x 81mm	IP44
PAR/SQ3/19.5W/4K	19.5	2100	840	∅ 222mm x 85mm	∅ 213mm x 81mm	IP44
PAR/SQ3/30W/27K	30	2550	927	∅ 222mm x 85mm	∅ 213mm x 81mm	IP44
PAR/SQ3/24W/3K	24	2550	830	∅ 222mm x 85mm	∅ 213mm x 81mm	IP44
PAR/SQ3/24W/4K	24	2700	840	∅ 222mm x 85mm	∅ 213mm x 81mm	IP44

Key Features


- Low glare architectural downlight
- Discreet minimal bezel, die-cast from pure aluminium
- Matt black darklight baffle, developed to minimise glare
- Fitted with an integral IP44 protective lens as standard
- Precision moulded 40° reflector
- Tridonic LED engine and driver system
- Excellent thermally optimised 24 super-fin die-cast heatsink
- Short circuit, overload and temperature protection
- Life >55,000h L90/F10

Please select from the options below


Dali	/DA
Switch Dim / Mains	/SD
DSI	/DSI
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Narrow beam reflector 20°	/NB
Plaster-in bezel version	/PI
Ra90 High colour rendering	/9
Casambi wireless network (inc dim)	/BTC
White Bezel	/WBZ
Black Bezel	/BBZ
White Baffle	/WBF
Black Baffle	/BBF



Options




/ECO
SwitchDIM, DALI or DSI



/MDIM
Mains dimming



/NB
20° Narrow beam reflector




/EM
EM conversion



/EMD
Self test and DALI EM conversion



/EMi
EM conversion with integral indicator



/EMDi
DALI/self test EM conversion with integral indicator



/9
High colour rendering Ra90 LEDs




/BTC
Bluetooth / Casambi wireless control (inc dim)




/PI
Plaster-in bezel version (cut-out 81 x 81 mm) 132.0 only



/WSB
White softlight baffle



Product variations
Other colours and specifications available on request



Wall wash available



Round available

