



| Model Ref. | Power (tcW) | Lumens (P/W) | Luminaire Output (lm) | Colour | Dimension | Cut Out | IP Rating |
|------------|-------------|--------------|-----------------------|--------|----------------|---------|-----------|
| NEW/13W/3K | 13 | 103 | 1350 | 830 | ∅ 110mm x 30mm | 90mm | IP54 |
| NEW/13W/4K | 13 | 106 | 1390 | 840 | ∅ 110mm x 30mm | 90mm | IP54 |
| NEW/18W/3K | 18 | 102 | 1850 | 830 | ∅ 190mm x 30mm | 160mm | IP54 |
| NEW/18W/4K | 18 | 105 | 1892 | 840 | ∅ 190mm x 30mm | 160mm | IP54 |
| NEW/25W/3K | 25 | 101 | 2520 | 830 | ∅ 225mm x 34mm | 200mm | IP54 |
| NEW/25W/4K | 25 | 105 | 2610 | 840 | ∅ 225mm x 34mm | 200mm | IP54 |

Key Features

- IP54 commercial downlight
- Recessed opal PC diffuser
- Bezel finished in RAL9016
- Long life 50,000h
- Dimming, DALI and EM options
- Tridonic Driver as Standard

Please select from the options below

- Dali /DA
- Switch Dim / Mains /SD
- DSI /DSI
- Emergency /EM
- Dali Emergency /DA/EM
- DALI Emergency Empro /DA/EMPRO
- Black Bezel /BLK

