



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	IP Rating	Up / Down Light
LOM/15W/3K	15	108	1625	3000K	∅ 639mm x 194mm x 70mm	IP20	Up only
LOM/15W/4K	15	108	1625	4000K	∅ 639mm x 194mm x 70mm	IP20	Up Only
LOM/23W/3K	23	102	2350	3000K	∅ 639mm x 194mm x 70mm	IP20	Up Only
LOM/21W/4K	21	111	2350	4000K	∅ 639mm x 194mm x 70mm	IP20	Up Only
LOM/29W/3K	29	101	2950	3000K	∅ 639mm x 194mm x 70mm	IP20	Up Only
LOM/25W/4K	25	118	2950	4000K	∅ 639mm x 194mm x 70mm	IP20	Up Only

Key Features

- Professional wall mounted LED uplight
- Philips LED module and driver system
- Opal acrylic diffuser for homogeneous illumination
- Excellent luminaire efficacy of up to 116.3 lm/tcW
- Presence and daylight sensor options
- Integral emergency and dimming options
- Aids LG7 compliance

Please select from the options below

Dali	/DA
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Black Body	/BLK
Presence & Daylight Sensor	/PS/DS

