



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	Length	UGR Rating
HIL/UGR/750/3K	24	100	2400	3000K	∅ 50mm x 75mm	750mm	19
HIL/UGR/750/4K	24	101	2450	4000K	∅ 50mm x 75mm	750mm	19
HIL/UGR/1200/3K	40	100	4000	3000K	∅ 50mm x 75mm	1200mm	19
HIL/UGR/1200/4K	40	101	4050	4000K	∅ 50mm x 75mm	1200mm	19
HIL/UGR/1500/3K	50	100	5000	3000K	∅ 50mm x 75mm	1500mm	19
HIL/UGR/1500/4K	50	101	5050	4000K	∅ 50mm x 75mm	1500mm	19
HIL/UGR/2000/3K	70	100	7000	3000K	∅ 50mm x 75mm	2000mm	19
HIL/UGR/2000/4K	70	101	7050	4000K	∅ 50mm x 75mm	2000mm	19
HIL/UGR/2400/3K	80	100	8000	3000K	∅ 50mm x 75mm	2400mm	19
HIL/UGR/2400/4K	80	101	8050	4000K	∅ 50mm x 75mm	2400mm	19

Key Features

- Direct, extruded linear profile luminaire
- Low Glare Prismatic lens for office and LG7 compliance
- Suitable for surface mount or suspension fixing
- Finished in RAL 9006 grey as standard
- Available in 4 standard lengths
- Bespoke Lengths and lumen outputs on request
- Life up to >50,000 hours
- Efficacy up to 95 lm p / watt

Please select from the options below

Dali	/DA
Switch Dim / Mains	/SD
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Surface Mount	/SF
Suspended	/SUSP
Black Body	/BLK
White Body	/WHI

