



Model Ref.	Total Power (tcW)	Lumens (P/W)	Total Luminaire Output (lm)	Colour	Dimension	Cut Out	IP Rating
CULL/6W/3K/SQ2	18	114	2052	3000K	∅ 270mm x 115mm x 80mm	90mm x 260mm	IP65
CULL/6W/4K/SQ2	18	115	2070	4000K	∅ 270mm x 115mm x 80mm	90mm x 260mm	IP65
CULL/9W/3K/SQ2	27	122	3294	3000K	∅ 270mm x 115mm x 105mm	90mm x 260mm	IP65
CULL/9W/4K/SQ2	27	124	3360	4000K	∅ 270mm x 115mm x 105mm	90mm x 260mm	IP65
CULL/13W/3K/SQ2	39	127	4953	3000K	∅ 270mm x 115mm x 115mm	90mm x 260mm	IP65
CULL/13W/4K/SQ2	39	128	5010	4000K	∅ 270mm x 115mm x 115mm	90mm x 260mm	IP65
CULL/18W/3K/SQ2	54	111	5994	3000K	∅ 270mm x 115mm x 135mm	90mm x 260mm	IP65
CULL/18W/4K/SQ2	54	113	6150	4000K	∅ 270mm x 115mm x 135mm	90mm x 260mm	IP65

Key Features

- Professional downlight with a wide choice of options
- Single Colour Type
- Beam Spread 55 degree As Standard
- Power Factor 0.95
- 5 Year Warranty
- 50,000 Hours
- High Grade 6063 Aluminium Housing Material

Please select from the options below

Dali	/DA
Switch Dim / Mains	/SD
DSI	/DSI
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Black Bezel	/BLK

