



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	IP Rating	UGR Rating
ROB/3/12W/3K	12	95	1150	3000K	∅ 595mm x 73mm	IP44	22.2
ROB/3/12W/4K	12	95	1150	4000K	∅ 595mm x 73mm	IP44	22.4
ROB/3/15W/3K	15	93	1400	3000K	∅ 595mm x 73mm	IP44	22.9
ROB/3/15W/4K	15	93	1400	4000K	∅ 595mm x 73mm	IP44	23
ROB/3/16W/3K	16	114	1825	3000K	∅ 595mm x 73mm	IP44	23.7
ROB/3/16W/4K	16	114	1825	4000K	∅ 595mm x 73mm	IP44	24
ROB/3/19W/3K	19	110	2100	3000K	∅ 595mm x 73mm	IP44	24.2
ROB/3/19W/4K	19	110	2100	4000K	∅ 595mm x 73mm	IP44	24.4
ROB/3/22W/3K	22	105	2325	3000K	∅ 595mm x 73mm	IP44	24.6
ROB/3/22W/4K	22	105	2325	4000K	∅ 595mm x 73mm	IP44	24.8

Key Features

- Adaptable 600 x 600 LED illuminated modular
- Single IP44 window for linear and patterned lighting schemes
- Excellent uniform light distribution
- Tridonic LED and driver system for optimum performance
- Excellent efficacy to aid Part L compliance
- Life >60,000 hours (L70 / F10) with a 5 year warranty
- Short circuit, overload and temperature protection
- White as standard, other colours available on request

Please select from the options below

Dali	/DA
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
DSI	/DSI
Switch Dim	/SD

