



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	IP Rating
GLE/PANEL/250	24	100	2400	3000K / 4000K	ø 250mm x 65mm	IP20
GLE/PANEL/300	30	100	3000	3000K / 4000K	ø 300mm x 65mm	IP20
GLE/PANEL/350	36	100	3600	3000K / 4000K	ø 350mm x 65mm	IP20
GLE/PANEL/400	42	100	4200	3000K / 4000K	ø 400mm x 65mm	IP20
GLE/PANEL/450	48	100	4800	3000K / 4000K	ø 450mm x 65mm	IP20
GLE/PANEL/600	60	100	6000	3000K / 4000K	ø 600mm x 65mm	IP20
GLE/PANEL/800	72	100	7200	3000K / 4000K	ø 800mm x 65mm	IP20
GLE/PANEL/900	84	100	8400	3000K / 4000K	ø 900mm x 65mm	IP20
GLE/PANEL/1000	96	100	9600	3000K / 4000K	ø 1000mm x 65mm	IP20
GLE/PANEL/1200	120	100	12000	3000K / 4000K	ø 1200mm x 65mm	IP20

Key Features

- Contemporary LED ring pendant
- High quality extruded aluminium body
- Available in various sizes
- Opal diffuser for consistent illumination
- 2m suspension wires option, longer if required
- Dimming options available
- Compliments the Gale Ring - contemporary LED ring pendants

Please select from the options below

Dali	/DA
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Black	/BLK
White	/WHI
Surface	/SFM
Suspended	/SUSP

