



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	Cut Out	IP Rating
CULL/6W/3K/SQ4	6	114	684	3000K	∅ 100mm x 85mm	90mm	IP65
CULL/6W/4K/SQ4	6	115	690	4000K	∅ 100mm x 85mm	90mm	IP65
CULL/9W/3K/SQ4	9	122	1098	3000K	∅ 100mm x 112mm	90mm	IP65
CULL/9W/4K/SQ4	9	124	1120	4000K	∅ 100mm x 112mm	90mm	IP65
CULL/13W/3K/SQ4	13	127	1651	3000K	∅ 100mm x 122mm	90mm	IP65
CULL/13W/4K/SQ4	13	128	1670	4000K	∅ 100mm x 122mm	90mm	IP65
CULL/18W/3K/SQ4	18	111	1998	3000K	∅ 100mm x 135mm	90mm	IP65
CULL/18W/4K/SQ4	18	113	2050	4000K	∅ 100mm x 135mm	90mm	IP65

Key Features

- Professional downlight with a wide choice of options
- Single Colour Type
- Beam Spread 55 degree As Standard
- Power Factor 0.95
- 5 Year Warranty
- 50,000 Hours
- High Grade 6063 Aluminium Housing Material

Please select from the options below

Dali	/DA
Switch Dim / Mains	/SD
DSI	/DSI
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Black Bezel	/BLK

