



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	Length
HIL/REC/600/3K	20	94	1850	3000K	∅ 90mm x 40mm	600mm
HIL/REC/600/4K	20	95	1900	4000K	∅ 90mm x 40mm	600mm
HIL/REC/1200/3K	40	94	3750	3000K	∅ 90mm x 40mm	1200mm
HIL/REC/1200/4K	40	95	3800	4000K	∅ 90mm x 40mm	1200mm
HIL/REC/1500/3K	50	94	4700	3000K	∅ 90mm x 40mm	1500mm
HIL/REC/1500/4K	50	95	4750	4000K	∅ 90mm x 40mm	1500mm
HIL/REC/1800/3K	60	94	5685	3000K	∅ 90mm x 40mm	1800mm
HIL/REC/1800/4K	60	95	5700	4000K	∅ 90mm x 40mm	1800mm
HIL/REC/2400/3K	80	94	7550	3000K	∅ 90mm x 40mm	2400mm
HIL/REC/2400/4K	80	95	7600	4000K	∅ 90mm x 40mm	2400mm

Key Features

- Recessed, extruded linear profile luminaire
- Low glare prismatic lens option for LG7 compliance, see our Hilton 7575
- Available in 4 standard lengths
- Bespoke Lengths and lumen outputs on request
- Life up to >50,000 hours
- Efficacy up to 95 lm p / watt

Please select from the options below

Dali	/DA
Switch Dim / Mains	/SD
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Black Body	/BLK
White Body	/WHI

