



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	IP Rating	UGR Rating
ROB/4/32W/3K	32	92	2975	3000K	∅ 589mm x 593mm x 100mm	IP44	18.2
ROB/4/32W/4K	32	100	3200	4000K	∅ 589mm x 593mm x 100mm	IP44	18.5
ROB/4/31W/3K	31	109	3400	3000K	∅ 589mm x 593mm x 100mm	IP44	18.7
ROB/4/31W/4K	31	115	3575	4000K	∅ 589mm x 593mm x 100mm	IP44	18.8
ROB/4/46W/3K	46	105	4875	3000K	∅ 589mm x 593mm x 100mm	IP44	19.9
ROB/4/46W/4K	46	111	5125	4000K	∅ 589mm x 593mm x 100mm	IP44	20.1
ROB/4/52W/TW	52	74	3875	830-860	∅ 589mm x 593mm x 100mm	IP44	N/A

Key Features

- Direct / indirect 600 x 600 LED modular to suit T24 exposed T ceiling grid
- Micro prismatic central diffuser
- Philips LED and driver combination
- Life up to >100,000h L70/B10
- Low glare version for LG7 compliance
- No visible flicker (IEEE 1789 - 2015)
- Highly efficient ECA compliant versions
- High output version 5125 Llm
- Tridonic HCL tunable white version
- Wireless, dimming and emergency options

Please select from the options below

Dali	/DA
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Suspended	/SUSP
Surface	/SF
Plasterboard Frame	/PB
Casambi	/CSB

