



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	Cut Out	IP Rating
BRA/M/10W/3K	10	98	975	830	∅ 150mm x 130mm	140mm	IP20
BRA/M/10W/4K	10	105	1050	840	∅ 150mm x 130mm	140mm	IP20
BRA/M/16W/3K	16	103	1650	830	∅ 150mm x 130mm	140mm	IP20
BRA/M/16W/4K	16	110	1775	840	∅ 150mm x 130mm	140mm	IP20
BRA/M/27W/3K	27	90	2450	830	∅ 150mm x 130mm	140mm	IP20
BRA/M/27W/4K	27	97	2625	840	∅ 150mm x 130mm	140mm	IP20

Key Features

- MINI high output, low glare LED scoop
- Fully adjustable die cast body
- Philips LED and driver system
- Premium White Ra90 LED module as standard
- 24° reflector as standard with 12° and 40° options
- No visible flicker (IEEE 1789 - 2015)
- ECA and Part L compliant variants
- Life >50,000h L70/B10
- 5 year warranty

Please select from the options below

Dali	/DA
Touch Dim	/TD
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
12 Deg Narrow Beam	/20
40 Deg Wide Beam	/40

