



- Lockable Track Mounted Emergency LED
- Available in RAL9005 (Black)
- Available in RAL9016 (White)
- Available as Standard or DALI Self-Test
- Powered by Long Life LiFePO4 Batteries
- 209 Lumen Output
- Suitable for Global Trac Systems
- Suitable for Eutrac Systems
- Suitable for Stucchi Systems
- DALI Track Adaptor
- Ingress Protection of IP20

There are 3 versions available -

Our Gould track is a 3 hour Non-Maintained Emergency LED unit which is designed as a discrete and simple emergency lighting solution to track fed lighting schemes.

In keeping with the emergency lighting standards, the product is locked in place, inhibiting post installation relocation. This retains the agreed emergency lighting scheme with even the most flamboyant of store merchandisers.

There are two main versions, available, standard emergency operation, and DALI self-test operation. Both types are available in white (RAL9016) and black (RAL9005).

The product is compatible with both Global Trac, Eutrac and Stucchi Systems.

Order Codes

GOUD/EM/NM3/* Non-Maintained with standard 3-hour emergency operation (* = B for Black and W for White)

GOUD/EM/DA/* Non-Maintained with 3-hour DALI self-test operation (* = B for Black and W for White)

Technical Details:

	GOUD/EM	GOUD/EM/DA
Input Voltage		230-240V AC 50/60Hz
Power Rating Charging **	2W 25mA $\lambda = 0.35$	2.2W 18mA $\lambda = 0.48$
Power Rating Charged **	0.45W 7.5mA $\lambda = 0.24$	0.4W 8.5mA $\lambda = 0.16$
Dimensions		330mm x 50mm x 85mm
Battery Type	3.2V 3.8Ah LiFePO4	3.2V 3.8Ah LiFePO4
Overall Weight	1.4Kg	1.4Kg
Ambient Temperature (Ta)		0 to 25°C

** LiFePO4 modules initially charge and then spend 90% of their operational life in the 'Charged' or standby state.

