




Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	Connecting Parts	IP Rating
GLE/RING/450	20	110	2200	830/840	∅ 450mm x 60mm x 60mm	1	IP20
GLE/RING/660	30	110	3300	830/840	∅ 660mm x 60mm x 60mm	1	IP20
GLE/RING/780	35	110	3850	830/840	∅ 780mm x 60mm x 60mm	1	IP20
GLE/RING/900	40	110	4400	830/840	∅ 900mm x 60mm x 60mm	1	IP20
GLE/RING/1060	50	110	5500	830/840	∅ 1060mm x 60mm x 60mm	1	IP20
GLE/RING/1200	60	110	6600	830/840	∅ 1200mm x 60mm x 60mm	1	IP20
GLE/RING/1560	80	110	8800	830/840	∅ 1560mm x 60mm x 60mm	4	IP20
GLE/RING/1860	110	110	12100	830/840	∅ 1860mm x 60mm x 60mm	4	IP20
GLE/RING/2060	120	110	13200	830/840	∅ 2060mm x 60mm x 60mm	4	IP20
GLE/RING/2460	150	110	16500	830/840	∅ 2460mm x 60mm x 60mm	4	IP20

Key Features

- Contemporary LED ring pendant
- High quality extruded aluminium body
- Available in various sizes
- Opal diffuser for consistent illumination
- 2m suspension wires option, longer if required
- Dimming options available
- Compliments the Gale Panel - contemporary LED moon pendants

Please select from the options below

Dali	/DA
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Black	/BLK
White	/WHI
Surface	/SFM
Suspended	/SUSP



W60xH60mm

