



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	Beam Angle	IP Rating
<b>GOUD/D/35W/3K</b>	35	102	3570	3000K	∅ 100mm x 85mm	20-55	IP20
<b>GOUD/D/35W/4K</b>	35	105	3675	4000K	∅ 100mm x 85mm	20-55	IP20
<b>GOUD/D/35W/3K/DALI</b>	35	102	3570	3000K	∅ 100mm x 112mm	20-55	IP20
<b>GOUD/D/35W/4K/DALI</b>	35	105	3675	4000K	∅ 100mm x 112mm	20-55	IP20

### Key Features

- Professional track downlight with a wide choice of options
- Single Colour Type
- Beam Spread 20-55 degree Adjustable
- Power Factor 0.95
- 5 Year Warranty
- 50,000 Hours
- High Grade 6063 Aluminium Housing Material

### Please select from the options below

- Emergency** /EM
- Dali Emergency /DA/EM
- Dali Emergency Empro** /DA/EMPRO
- White /WHI
- Live End** /LE
- End Cap /EC
- Straight Connector** /SC
- 90 Degree Connector /90
- Flexible Connector** /FC
- Tee Connector /TEE
- Suspension Kit** /SUSP
- Honeycomb Baffle /HB



Narrow beam reflector



Wide beam reflector

