



Model Ref.	Power (tcW)	Lumens (P/W)	Luminaire Output (lm)	Colour	Dimension	Length
HIL/UGR/600/3K	20	94	1850	3000K	∅ 75mm x 75mm	600mm
HIL/UGR/600/4K	20	95	1900	4000K	∅ 75mm x 75mm	600mm
HIL/UGR/1200/3K	40	94	3750	3000K	∅ 75mm x 75mm	1200mm
HIL/UGR/1200/4K	40	95	3800	4000K	∅ 75mm x 75mm	1200mm
HIL/UGR/1500/3K	50	94	4700	3000K	∅ 75mm x 75mm	1500mm
HIL/UGR/1500/4K	50	95	4750	4000K	∅ 75mm x 75mm	1500mm
HIL/UGR/2400/3K	80	94	7550	3000K	∅ 75mm x 75mm	2400mm
HIL/UGR/2400/4K	80	95	7600	4000K	∅ 75mm x 75mm	2400mm

## Key Features

- Direct, extruded linear profile luminaire
- Low Glare Prismatic lens for office and LG7 compliance
- Suitable for surface mount or suspension fixing
- Finished in RAL 9006 grey as standard
- Available in 4 standard lengths
- Bespoke Lengths and lumen outputs on request
- Life up to >50,000 hours
- Efficacy up to 95 lm p / watt

## Please select from the options below

Dali	/DA
Switch Dim / Mains	/SD
Emergency	/EM
Dali Emergency	/DA/EM
DALI Emergency Empro	/DA/EMPRO
Surface Mount	/SF
Suspended	/SUSP
Black Body	/BLK
White Body	/WHI

